

The Giganet Lockable IP65 & UV Resistant distribution box is supplied unloaded as standard and offers the ability to terminate 24 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 24 SC simplex connections and splices. The box has 24 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating.



FEATURES

- UP to 24 splice with SC Simplex Adapter.
- Lockable Door for security.
- IP65 & UV Resistant.
- Accepts loose tube, distribution and pre-terminated cables
- Removable splice tray for easy installation.
- Integrated bend radius protection
- ROHS, REACH & SvHC compliant.
- Data communication Networks.
- Indoor/Outdoor Application.
- FTTH / FTTx Networks.

TECHNICAL SPECIFICATION

Parameters	Value
Width	270mm
Height	340mm
Depth	110mm
N° of Port	24 SC Simplex
Max. Splicing Capacity	24 Splices
Net Weight (Kg)	1.8
Material	ABS
Operating Temperature	-40 °C +60°C
Cable entry	2 (up to 13mm OD)
Color	Grey RAL7035
Compliant to	RoHS, REACH, SvHC

PRODUCT INFORMATION

Part Number	Product Description
GN-WP-24-U1	Giganet IN/OUT Lockable Wall Box IP65 UV Resistant 24 Position SC Simplex Unloaded