



IEC60309 plug (32A 2P+E)

Main	Description	
Socket Type	Iec 320 C19 standard, press (right)[2];Single IEC320 C13 Socket(Right)[8];	
Power Input	10 Way	
Socket Quantity	Left end single input (Bottom feed power input)	
Bracket Install	Inverse installation (0U)	
Cable with plug	IEC60309 plug (32A 2P+E) [Legrand]	
Control Function	No controlling function	
Protection Function	Build-in Amps/Volts LED ammeter	
Case	Black	
Cable Specification	3 x 2.5 mm ² x 3M	
Product Size	L x W x H = 630 x 50 x 44.4 mm	
Mounting Length	609 mm	
Case Length	577 mm	
PDU Exponent	0.721	
Product Label	Product Name	Designated Power Distribution Unit for Cabinet
	Specification Model	GN-PDU-M1V080225032
	Rating voltage	100~250VAC 50/60Hz
	Rating Current	
	Max. Current	32A
	Max. Power	8000W
	Safety Authentication	CE
Socket assemble	NO	
Interior Connection Wire	2.5 mm ² (14AWG)	
Interior Connection Style	Integration of copper strips	
Fix the Cable	Cable clamp (19)	

Ordering Information

Part Number	Description
GN-PDU-M1V080225032	Giganet PDU Metered Vertical,C13x8,C19X2,250V/32A