



IEC60309 plug (32A 3P+N+E)

Main	Description	
Socket Type	Iec 320 C19 standard, press (right)[6];Single IEC320 C13 Socket(Right)[24];	
Power Input	30 Way	
Socket Quantity	Left end single input (Bottom feed power input)	
Bracket Install	Inverse installation(OU)	
Cable with plug	IEC60309 plug (32A 3P+N+E) [Legrand]	
Control Function	No controlling function	
Protection Function	Build-in Amps/Volts LED ammeter	
Case	Black	
Cable Specification	5 x 6.0 mm ² x 3M	
Product Size	L x W x H =1479 x 50 x 44.4 mm	
Mounting Length	1458 mm	
Case Length	1426 mm	
PDU Exponent	1.649	
Product Label	Product Name	Designated Power Distribution Unit for Cabinet
	Specification Model	GN-PDU-M3V240640032
	Rating voltage	380~400VAC 50/60Hz
	Rating Current	
	Max. Current	3x 32A
	Max. Power	22kW
	Safety Authentication	CE
Socket assemble	NO	
Interior Connection Wire	4.0 mm ² (14AWG)	
Interior Connection Style	Integration of copper strips	
Fix the Cable	Cable clamp (19)	

Ordering Information

Part Number	Description
GN-PDU-M3V240640032	Giganet PDU Metered Vertical,C13x24,C19X6,400V/32A